



DUNNAIR
(Aust) Pty Ltd

Large Capacity Fan Coil Unit

Ceiling Concealed

FCU60DF

Model Number Configuration

FCU60DF : Ceiling Concealed Model

PERFORMANCE DATA

RETURN AIR

Model	Row	Air Flow					Rated Cooling Capacity	Rated heating Capacity	Water Flow	Water Resist-ance	Noise	Input Power	Weight
		L/S											
		SH	HH	H	M	L	kW	kW	L/S	kPa	dB (A)	W	kg
FCU-60DF	3	281	256	233	211	169	5.7	8.6	0.33	47.41	54	230	42

Notes for Return Air :





1. Nominal condition is based on (GB/T19232-2003).
2. Cooling:Returnair temp.80.6 °F(27°C) DB,67.1°F(19.5°C) WB
3. Chilled water inlet temp .44.6 °F(7°C) ,water temp rise 41°F(5°C)
4. Heating:Return air temp .69.8(21°C) DB,chilled water inlet temp 140°F(60°C)
5. Water flow rating is as the same as cooling
6. Standard working pressure of fan coil units is 1.8 Mpa,if the requirement is over 1.8 Mpa, please indicate when ordering .

SPECIFICATION


- Forward curved centrifugal fan
- Single phase motor & direct drive
- Coils: Copper tube & Aluminum fins
- Galvanised sheet casing
- A3 steel sheet painting drip-tray

Ceiling Concealed

FCU60DF




- 1. Condensation 3/4MPPT
- 2. Water Inlet 3/4FPT
- 3. Water Outlet 3/4FPT

DRAWN BY:	DATE: 2009/10/12		SHEET SIZE: A4		
			ISSUE:		
APPROVED Q.A.:	APPROVED ENG.:	TITLE: Water Cooled Fan Coil Unit	FCU TYPE		
			DRAWING NO.:		
MODEL: FCU-60 DF			SCALE:		
			SHEET 1 OF 1		

Ceiling Concealed


FCU60DF



FAN COIL UNIT

Ceiling Concealed
FCU60DF

FAN CURVE



FAN COIL UNIT

Ceiling Concealed FCU60DF

NOISE CURVE

