

Super Slim Ceiling Mounted Air Handling Unit LFPS Series LFPS180

Model Number Configuration

LFPS180-4+1: 4 + 1 Row Super Slim Ceiling Mounted LFPS180-6+1: 6 + 1 Row Super Slim Ceiling Mounted

PERFORMANCE DATA

RETURN AIR

Model	Air Flow	4 Rows Cooling				1 Row Heating			External Excess						
		Total	Sensible	Water Flow	Water Resist ance	Rated Heating	Water Flow	Water Resista nce	Pressure			Motor Power			Weight
									I	II	III	I	II	Ш	
	l/s	kW	kW	l/s	kPa	kW	l/s	kPa	Pa	Pa	Pa	kW	kW	kW	kg
LFPS180-4+1	5000	100.0	72.3	4.8	17.6	53.1	1.3	15.3	300	400	500	5.5	7.5	7.5	489.6
LFPS180-6+1	5000	125.7	86.5	6.0	12.9	53.1	1.3	15.3	300	400	500	5.5	7.5	7.5	542.6

Notes for Return Air:

- 1. Cooling: The water in/out temp.is 7°C/12°C; the air in temp. is 27°C DB / 19.5°C WB
- 2. Heating: The water in temp. is 80°C / 50°C; the air in temp. is 21°C DB..
- 3. The motor power offered is the motor output power.
- 4. The above performance is for reference only. Different air and water conditions would lead to different cooling capacity.

SPECIFICATION

• Coil:

LFPS010W-LFPS 120W : ϕ 9.52mm, copper tube, aluminium fins LFPS135W-LFPS 300W: ϕ 12.7mm, copper tube, aluminium fins


• Fan and motor:

LFPS 010W-LFPS025W: direct driven, forward curved centrifugal fan LFPS 030W-LFPS 300W: belt driven, forward curved centrifugal fan

• Filter: 15mm panel filter


Cabinet: 25mm thick double skinned panel

Drip-tray: powder painting steel sheet




Wiring Diagram

415V/3Ph/50Hz



Super Slim Ceiling Mounted Air Handling Unit LFPS180

FAN CURVE





Super Slim Ceiling Mounted Air Handling Unit LFPS180

NOISE CURVE

